

LED Under Cabinet Light



01

CB CE ErP 



No Flicker



Dimmable Option



Ra80



25000h



S: AC 85-265V



For Indoor



320°



Warm Light
3000K







Natural Light
4000K



White Light
6500K

Features :

-  Aluminum Casing / PC Diiffuser / ABS End Caps
-  Charging Cable: Type C Cable
-  Installation: Magnetic Adhesive Plate x 2
-  Functions: M1: 100% Always On
M2: Night&IR Sensor Trigger
M3: SOS Flash Mode



Model No. 产品规格	Dimension WxHxL (mm)	Rated Power 额定功率	Battery Capacity 电池容量	Lumen 流明	Color Temp. 色温	PCS/CTN 装箱数量	CTN MEAS. 装箱尺寸(cm)
XGYUCL-ZO-100GYD-CCT-E1	100*18.5*17	0.5W	200mAh	30lm Stepless Dimming	3000K-6500K	154	43*21.5*27.5
XGYUCL-ZO-150GYD-CCT-E1	150*18.5*17	0.5W	280mAh	42lm Stepless Dimming	3000K-6500K	168	52*22*28.5
XGYUCL-ZO-210GYD-CCT-E1	210*18.5*17	1W	350mAh	60lm Stepless Dimming	3000K-6500K	100	33.5*31.5*25
XGYUCL-ZO-297GYD-CCT-E1	297*18.5*17	1W	450mAh	88lm Stepless Dimming	3000K-6500K	100	43*31.5*24
XGYUCL-ZO-500GYD-CCT-E2	500*18.5*17	2W	900mAh	140lm Stepless Dimming	3000K-6500K	80	63.5*25*25.5



Warm Light
3000K

Natural Light
4000K

White Light
6500K

Features :

- ✘ Aluminum Casing / ABS End Caps / PMMA Lens
- ✘ Charging Cable: Type C Cable
- ✘ Installation: Magnetic Adhesive Plate x 2
- ✘ Functions: M1: 100% Always On
M2: Night&IR Sensor Trigger



Model No. 产品规格	Dimension WxHxL (mm)	Rated Power 额定功率	Battery Capacity 电池容量	Lumen Efficacy 光效	Color Temp. 色温	PCS/CTN 装箱数量	CTN MEAS. 装箱尺寸(cm)
XGYUCL-ZO-CAJMYGYD-200-CCT-E2	200*40*11	0.5W	600mAh	100lm/W Slide Switch 3 Step	3000K-6500K	99	43*21.5*27.5
XGYUCL-ZO-CAJMYGYD-300-CCT-E4	300*40*11	0.8W	900mAh	100lm/W Slide Switch 3 Step	3000K-6500K	100	63.5*25*25.5
XGYUCL-ZO-CAJMYGYD-400-CCT-E4	400*40*11	1.2W	1200mAh	100lm/W Slide Switch 3 Step	3000K-6500K	49	43*21.5*27.5
XGYUCL-ZO-CAJMYGYD-600-CCT-E5	600*40*11	1.2W	1500mAh	100lm/W Slide Switch 3 Step	3000K-6500K	50	63.5*25*25.5



Warm Light
3000K

Natural Light
4000K

White Light
6500K

Features :

- ✘ Aluminum Casing / PC Diiffuser / ABS End Caps
- ✘ Charging Cable: Type C Cable
- ✘ Installation: Magnetic Adhesive Plate x 2
- ✘ Functions: M1: 100% Always On
M2: Night&IR Sensor Trigger



Model No. 产品规格	Dimension WxHxL (mm)	Rated Power 额定功率	Battery Capacity 电池容量	Lumen Efficacy 光效	Color Temp. 色温	PCS/CTN 装箱数量	CTN MEAS. 装箱尺寸(cm)
XGYUCL-ZO-CAJGYD-200-SS-E2	200*40*11	1.6W	600mAh	100lm/W Stepless Dimming	3000K-6500K	99	43*21.5*27.5
XGYUCL-ZO-CAJGYD-300-SS-E2	300*40*11	2.1W	900mAh	100lm/W Stepless Dimming	3000K-6500K	100	63.5*25*25.5
XGYUCL-ZO-CAJGYD-400-SS-E3	400*40*11	2.6W	1200mAh	100lm/W Stepless Dimming	3000K-6500K	49	43*21.5*27.5
XGYUCL-ZO-CAJGYD-600-SS-E3	600*40*11	3W	1500mAh	100lm/W Stepless Dimming	3000K-6500K	50	63.5*25*25.5



Warm Light
3000K



Natural Light
4000K



White Light
6500K

Features :

- ✘ Aluminum Casing / PC Diiffuser / End Caps
- ✘ Charging Cable: Type C Cable
- ✘ Installation: Magnetic Adhesive Plate
- ✘ Functions: M1: 100% Always On
M2: Night&IR Sensor Trigger



Model No. 产品规格	Dimension WxHxL (mm)	Rated Power 额定功率	Battery Capacity 电池容量	Lumen Efficacy 光效	Color Temp. 色温	PCS/CTN 装箱数量	CTN MEAS. 装箱尺寸(cm)
XGYUCL-TQT088-20CM-E1	14.2*40*206	1W	1000mAh	100lm/W Remote Dimming	3000K-6500K	50	34*23.5*27
XGYUCL-TQT088-30CM-E1.5	14.2*40*306	1.5W	1500mAh	100lm/W Remote Dimming	3000K-6500K	50	34*32.5*27
XGYUCL-TQT088-40CM-E2	14.2*40*406	2W	2200mAh	100lm/W Remote Dimming	3000K-6500K	50	42.5*34*17



Warm Light
3000K



Natural Light
4000K




White Light
6500K

Features :


- ✘ Full ABS
- ✘ Charging Cable: Type C Cable
- ✘ Installation: Magnetic Adhesive Plate x 2
- ✘ Functions: M1: 100% Always On
M2: Night&IR Sensor Trigger




Model No. 产品规格	Dimension WxHxL (mm)	Rated Power 额定功率	Battery Capacity 电池容量	Lumen Efficacy 光效	Color Temp. 色温	PCS/CTN 装箱数量	CTN MEAS. 装箱尺寸(cm)
XGYUCL-ZO-LED-210MM-CCT-E7	210*38*23	3W	1200mAh	100lm/W Stepless Dimming	3000K-6500K	88	33.5*31.5*26
XGYUCL-ZO-LED-297MM-CCT-E11	297*38*23	3W	1800mAh	100lm/W Stepless Dimming	3000K-6500K	64	33.5*31.5*26



Warm Light
3000K



Natural Light
4000K



White Light
6500K

Features :

- ✘ ABS Casing / PC Diiffuser / End Caps
- ✘ Charging Cable: Type C Cable
- ✘ Installation: Magnetic Adhesive Plate
- ✘ Functions: M1: 100% Always On
M2: Night&IR Sensor Trigger



Model No. 产品规格	Dimension WxHxL (mm)	Rated Power 额定功率	Battery Capacity 电池容量	Lumen Efficacy 光效	Color Temp. 色温	PCS/CTN 装箱数量	CTN MEAS. 装箱尺寸(cm)
XGYUCL-TQT013-E1	29*40*300	1.5W	2000mAh	100lm/W Remote Dimming	3000K-6500K	50	39*32.5*27